

EASY INSTALL MINI DOMES



	INDOOR EASY INSTALL MINI PTZ	INDOOR EASY INSTALL IR FIXED MINI	INDOOR EASY INSTALL MINI PTD
	MPTZ5XFM	MF21M4TIRFM	MPTDFM
Sensor	1/2.8 2.0M Sony CMOS		
Compression format	Triple Codec, H.264/MPEG4/MJPEG		
Max. resolution	1080p / 720p / D1/ CIF / QCIF (MJPEG)		
Effective pixels	1920 x 1080		
Compression FPS	30/25 fps Max. frame rate for all resolutions		
Lens	5 ~ 25mm, F3.5 ~ F3.7 5x Optical Zoom / 12x Digital Zoom	4mm 12x Digital Zoom	4mm 12x Digital Zoom
Horizontal FOV	49.2° W ~ 10.52° T	86°	86°
Iris control	Manual Fixed		
S/N ratio	True WDR 100dB		
Video output	-		
Alarm in-/output	1 / 1		
Audio in-/output	1 / 1		
Audio codec	Two way, G.711 PCM. μ -law 64kbps 8kHz		
Day/Night Performance	True Day/Night		
Minimum illumination	Color: 2.8 Lux@ F3.5, 30 IRE B/W: 0.9 Lux @ F3.5, 30 IRE	12.4 Lux (F1.6, 30IRE), 0.5 Lux 30IRE), IR (F1.6, 0.00 Lux (IR LED ON))	Color: 2.4 Lux@ F1.6, 30 IRE B/W: 0.5 Lux@ F1.6, 30 IRE
Dewarping	-		
Pan / Tilt Range	Pan: 355° / Tilt 90° / Rotate 350°	-	Pan: 355° / Tilt 90° / Rotate 350°
Pan / Tilt Speed	Preset: 120° / sec, manual: Max 120° / sec	-	Preset: 120° / sec, manual: Max 120° / sec
Network interface	10/100 Base T		
Protocols	1Pv4/1Pv6, TCP/IP, RTP Multicast. liTTP, DHCP, PPPoE, ICMP, ARP, RARP, RTSP, NTP, SNMP, SMTP, FTP, UPnP, DNS, DNS		
Web Browser	Internet Explorer 7.0 or above, Firefox, Chrome, PDF / Smart Phone		
Edge storage (not included)	SDHC memory card (card is not included)		
Motion detection	Notification: FTP, email, Alarm out, JPEG Recording on SD		
Power source	12VDC / PoE		
PoE	Support (IEEE 802.3af)		
Power consumption	6W (Idle) / 9W (Operating)	4W (IR Off), 5W (IR on)	5.6W (Idle) / 8.2W (Operating)
Operating environment	14° F ~122° F / -10°C ~ 50°C		
Housing / Color / IR	Drop Ceiling /Quick Installation	Drop Ceiling /Quick Installation. 15 IR LEDs	Drop Ceiling /Quick Installation
Weight	0.8 lbs. / 363g	1.1 lbs./ 500g	1.1 lbs./ 500g
Dimensions	5.9" H x 4.3" \varnothing /149.2 H x 110mm \varnothing	4.5" x 3.5" \varnothing / 114mm H x 90mm \varnothing	5.9" \varnothing x 4.3" /149.2 \varnothing x 110mm
Certifications	ONVIF (Profile S), CE, FCC, ROHS		