



STARVIS

1080p IR IP Mini Dome with GXi Analytics

GANZ WITH **GXi**
PixelPro
TECHNOLOGY

ZN1A-M4DTFN3

Features:

- 1080p @ 30fps
- 1/2.8" SONY STARVIS Exmor Sensor
- True Day / Night and WDR
- 2.8mm Fixed Lens
- VCA Technology Video Analytics
- Superior Low Light Performance
- SMART Bitrate Control & Region of Interest
- 2 IR LEDs up to 59' Range

ZN1A-M4DTFN3

1080p IR IP Mini Dome with GXi Analytics

■ Specifications (Part 1)

Model		ZN1A-M4DTFN3
Camera	Image Sensor	1/2.8" SONY STARVIS Exmor 2.13MP CMOS
	Effective Pixels	1920 x 1080
	Scanning System	Progressive scanning
	AGC Control	Auto
	Iris Type	Auto-Iris
	Minimum Illumination	Color: 0.03 Lux (DSS on) / B/W : 0 Lux (IR on)
	Lens	2.8mm, F2.0 Fixed Lens
	Angle of View	Horizontal: Approx. 115° / Vertical Approx. 64°
	Shutter Speed	Automatic / Manual: 1/30 ~ 1/32,000, Anti-Flicker, Slow Shutter (1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10)
	Day/Night Performance	True Day / Night (ICR)
	Wide Dynamic Range	True WDR, 120dB
	S/N Ratio	50 dB
Video	Video Compression	H.265, H.264 Baseline, Main, High profile, MJPEG (Motion JPEG)
	Multiple Profile Streaming Performance	2592 x 1944 @30fps & 480 @30 fps with H.264, H265 & MJPEG
	Max Resolution	1920 x 1080
	Video Bit Rate	100Kbps ~ 10Mbps Multi-rate for Preview and Recording
	Bit Rate Control	Multi Streaming CBR/VBR @ H.264 (Controllable frame rate and Bandwidth)
	Digital Noise Reduction	3D-DNR
	ROI (Region of Interest)	Supported
	SMART Bitrate Control	Supported
	Other Image Processing	Configurable Exposure, White Balance, Sharpness
Privacy Mask	16 programmable zones	
Audio	Audio Streaming	Two Way
	Audio Compression	G.711
	Audio Input / Output	1 (Built-In Mic) / 0
Event	Event Trigger	Motion, Temperature critical
	Pre-Post Recording	Pre: 1~5 sec / Post: 1~240 sec
	Event Notification	FTP, E-mail, SD card
Network	Ethernet Standard	10 / 100 Base-T
	IP	IPv4
	Protocol	TCP/IP, UDP, AutoIP, RTP(UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3(MIB-2), ONVIF
	Security	HTTPS (SSL), IP Filtering, 802.1x, Digest Authentication
	Plug In	ONVIF Profile S, CGI API

All specifications are subject to change without notice.

ZN1A-M4DTFN3

1080p IR IP Mini Dome with GXi Analytics

■ Specifications (Part 2)

Model		ZN1A-M4DTFN3
Analytics (standard)	Analytics Engine	Advanced tracking algorithm with rich library of detection behaviors
	Detection Zones	40 zones (Multi-segment Polygons and Lines) in total
	Rules	60 rules in total
	Tamper Detection	Supported
Analytics (optional)	Detection Behavior	Enter, Exit, Appear, Disappear, Stop, Direction, Dwell filter; Tailgating; Color Filter
	Logic Rules	Extends standard rules to allow various combinations of the inputs
	3D Behavior	Perspective Corrected Size and Speed Filters
	Object Classification	Configured Max./Min. object sizes and Max./Min. speeds
	People Tracking	Tracks individuals separately among overlapped multiple people
	Counting	20 counters in total
	Counting Line	High accuracy people and vehicle counting
	Counter Report	Generates counter reports based on the counter database
	Heatmap Report	Shows relative crowd density of the 24 hour period (criterion: midnight)
	Meta Data	JSON format, Plain XML Format
Edge Storage	Storage	1x MicroSD memory card slot / microSDHC / microSDXC (card not included)
Physical	Material	Aluminum Die-Casting; White
	Language	English
	IR LEDs	2 Smart IR LEDs (59' Range)
	Power Source	12VDC, PoE (IEEE 802.3af)
	Power Consumption	12VDC Max. 3.7W / PoE Max 5.5W
	Operating Conditions	[12VDC/PoE] -4°F ~ 122°F (-20°C ~ 50°C) / Humidity 10% to 90% RH (non-condensing)
	Dimensions	4.1" (Ø) x 2.4" / 105mm (Ø) x 60.7mm
	Weight	0.9 lbs / (400g)
	Certifications	FCC, CE, IP67, Onvif S

All specifications are subject to change without notice.