



1080p AHD Outdoor Hybrid IR Motorized Dome





Z8-VD2M-2

Features:

- 1/2.8" SONY Progressive Scan CMOS
- 2.8-12mm Motorized Lens
- Full HD 1080p @30fps
- 4-in-one AHD/TVI/CVI/CVBS
- True Day/Night
- 984' (300m) Video Transmission
- IR Range 98'
- 3D DNR, WDR, ICR, BLC
- IP67, IK10

Accessories

ZA8-CBK625	ZA8-CBK624
Pendant Mount	Wall Mount
	

Z8-VD2M-2

1080p AHD Outdoor Hybrid IR Motorized Dome

■ Specifications

Model	Z8-VD2M-2
Image Sensor	1 / 2.8" Progressive Scan CMOS
Signal System	NTSC/PAL
Minimum Illumination	Color 0.001 Lux @ F1.2 (AGC ON) / B/W 0 LUX (IR LED ON)
S/N Ratio	>50dB
Day / Night Performance	True Day / Night (ICR)
Wide Dynamic Range	Digital WDR
Shutter Speed	NTSC:1/30s-1/10000s
Digital Noise Reduction	2D / 3D
Lens	2.8-12mm Motorized Focus
Iris	Fixed
Field of View	105° ~ 35°
IR LED	15 IR LEDs (98' Range)
IR Wavelength	850nm
OSD Joystick	Support
Up the Coax	Support
Max. Resolution	1920 x 1080 / 30fps
Alarm Trigger	Mirror, Defog, HLC, Privacy Masking, Motion Detection
Max Distance	75-5 984' (300m)
Video Output	AHD / TVI / CVI / CVBS
Power Supply	12VDC/24VAC ±10%
Power Consumption	4.5W (Max 12VDC, IR ON)
Operating Temperature	14 °F ~ 131 °F (-10 °C ~ 55 °C)
Operating Humidity	0% - 85% RH
Material	Metal
Dimensions	5.1" (Ø) x 4.4" / 130mm (Ø) x 112mm
Weight	1.5 lbs / 720g
Certifications	CE, FCC, IP67, IK10