



BH1 With Cover Removed



FEATURES

- B/W or Color options with 2.5 or 6mm fixed iris lens
- All camera options include backlight compensation and auto electronic shutter for indoor or outdoor use
- Wall, ceiling or corner mount with optional bracket
- Weather-sealed aluminum housing with 3/16 inch polycarbonate window and tamperproof key lock
- Mounting hardware and BNC connector included



BH1 Housing with Optional Corner Mount Bracket (model BH1-C)

MODEL	CAMERA	LENS	RESOLUTION	SENSITIVITY	VOLTAGE
BH1-MM25	B/W	2.5MM F2.0	380 LINES	0.3 LUX	12 VDC +- 10%
BH1-MMH25	HI-RES B/W	2.5MM F2.0	560 LINES	0.6 LUX	12 VDC +- 10%
BH1-CM25	COLOR	2.5MM F2.0	330 LINES	1.5 LUX	12 VDC +- 10%
BH1-CMH25	HI-RES COLOR	2.5MM F2.0	470 LINES	2.5 LUX	12 VDC +- 10%
BH1-C	OPTIONAL CORNER MOUNT ADAPTER				

Lens Options: 2.5mm or 6.0mm.

To order cameras with a 6.0mm lens, use suffix 60 instead of 25 (eg. BH1-CMH60)