



# ZN-D2024

## INDOOR FIXED NETWORK DOME



Model ZN-D2024  
with 2-4mm lens

GANZ™ ZN-D2024 network dome camera is ideal for indoor residential or commercial use. It has a 3-axis lens adjustment mechanism for wall or ceiling mount applications. The microchip technology generates a high quality video bitstream in both MPEG-4 and Motion JPEG formats. Two video streams with different configurations can be activated simultaneously to address the different requirements for live viewing and recording.

An 802.3af compliant Power over Ethernet (PoE) module is built-in to ease the installation process. Together with the free bundled 16-ch recording software, the ZN-D2024 is ideal for office and home security.

### F E A T U R E S

- Wide angle varifocal board lens
- 3-axis lens adjustment for wall mount application
- Real-time MPEG-4 and Motion JPEG compression
- Power over Ethernet (PoE) built-in
- Simultaneous dual-stream support



# IP CAMERAS

# ZN-D2024

INDOOR FIXED NETWORK DOME CAMERA



Model ZN-D2024  
with 2-4mm lens



DETAIL OF ZN-D2024 CONNECTIONS

## SPECIFICATIONS

### System and Hardware

- Flash: 8MB
- RAM: 64MB
- Lens: Varifocal board lens, 2mm-4mm, F1.4-F1.8

### Angle of View

- 53.2-105°
- Image Sensor: 1/4" CMOS
- Embedded OS: Linux 2.4

### Video

- Motion JPEG video with resolution up to 640x480
- MPEG-4 video with resolution up to 640x480 Frame rate: 30fps

### Audio

- GSM-AMR speech compression
- MPEG-4 AAC audio encoding
- 2-way audio with audio mute
- Bit rate: 4.75Kbps to 12Kbps
- Switch for built-in microphone and external microphone

### Streaming

- Simultaneously dual-streaming
- MPEG-4 streaming over UDP, TCP, or HTTP
- MPEG-4 multicast streaming
- M-JPEG streaming over HTTP

### Networking

- 10/100 Mbps Ethernet, RJ-45
- Protocols: TCP/IP, HTTP, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, Telnet, DHCP, NTP, DNS, DDNS, & PPPoE

### Event Management

- Multiple-window video motion detection
- 1 digital input and 1 digital output
- Event notification using HTTP, SMTP, or FTP

### Security

- Multi-level user access
- IP address filtering

### Power

- 12V DC
- Power over Ethernet: 802.3af compliant

### Applications

- Installation wizard
- 16-ch recording software
- SDK available for application development and system integration



CBC (AMERICA) Corp.

NEW YORK: 55 MALL DRIVE COMMACK, NY 11725 TEL: 1 (800) 422-6707 • (631) 864-9700 • FAX: (631) 543-5426  
CALIFORNIA: 20521 EARL STREET TORRANCE, CA 90503 TEL: 1 (800) 888-0131 • (310) 793-1500 • FAX: (310) 793-1506  
www.cbccamera.com GANZ® is a registered trademark of CBC (AMERICA) Corp. © 2008 CBC (AMERICA) Corp. All Rights Reserved. 01/08

