

Features:

- Optical 26x zoom endless PTZ Camera
- Removable IR cut filter for True Day/Night performance
- Built-in image stabilizer function
- 63 presets, 8 tours, 4 scan, 4 pattern and an auto-scan function
- Aluminum body & resistance lens cover
- All internal parts are corrosion protected epoxy powder coating
- IP66 Rated for all weather conditions (built-in fan & heater)
- 2 way position vector control
- Ideal for fire apparatus, police car and other specialty vehicles
- Compatible with 3 axis joystick PTZ controller (ZZ-WX444S)



ZZ-WE432

26X IR Endless PTZ Camera

Model	ZZ-WE432
Image Sensor	¼" Sony Super HAD CCD
Effective Pixels	680K
Lens	26x Zoom, f=3.5mm(wide) to 91.0 mm(tele), f1.6 to f3.8
S/N ratio	More than 50dB
Min. Illumination	0.7 Lux (typical, 30 IRE), 0.05 Lux (ICR model) 0.001 Lux (DSS B/W mode)
Pan	Angle: 0-360°(Endless), Manual Speed: More than 100°/sec, Preset Speed: More than 110°/Sec
Tilt	Angle: -20° to 90°, Manual Speed: More than 60°/sec
On-Screen Display	Camera ID, Camera name, area name and Preset number
Auto swing	Max. 4 pan Swing (2 Position Swing)
IR Distance	50m (IR LED type: 850nm)
Preset	63 Positions
Tour	8 Guard Tours, consisting of 63 presets and functions
ID (Camera Address)	0 ~ 255 address
Control	RS-485/RS-422C, baud rate: 2400/11520bps
Power Consumption	DC12V(DC11-18V), 50/60Hz 3A
Operating Temperature	-40° F ~ 131° F / -40° C ~ 55° C
Operating Humidity	30% - 90% RH
Certifications	CE, FCC
Dimensions / Weight	5.4" W x 8.1" H (138mm W x 205.8mm H) / 6.6lbs.. 3Kg