



ZC-EV600IR

Indoor/Outdoor Vandal-Resistant Mini Dome Camera

Features:

- Compact, vandal-resistant dome camera
- 600TVL
- Audio recording
- 11 IR illuminators for optimal low-light performance
- Easy installation on vehicle ceiling, wall, surface or flush mounted
- Standard and angled surface mounted adaptors available
- Ideal for vehicle & CCTV applications
- Polycarbonate dome cover
- IP66 rated for all outdoor weather conditions

Indoor/Outdoor Vandal-Resistant Dome Camera

ZC-EV600IR



ZC-EV600IR Surface and Flush Mount Views



■ Specifications

Model	ZC-EV600IR
Signal System	NTSC
Image Sensor	1/3" SONY Super HAD CCD
Total Effective Pixels	410K / 508K
Resolution	600TVL
Shutter Speed	1/60~1/100,000 sec.
Video Output	VBS 1.0Vp-p (75 Composite)
Sync. System	Internal
Scanning System	2:1 Interface
S/N Ratio	More than 50dB (AGC Off)
Min. Illumination	0.05 Lux
Audio	Audio Type
Housing Material	Vandal-resistant
Lens Rotation	3-axis mechanism
Lens	3.6mm fixed lens
Power Supply	12VDC
Operating Temp.	14° F~122°F (-10° C~+50° C)
Dimensions	3.3" Ø x 2.6" L (82.4mm Ø x 66.4mm L)
Weight	0.9lbs (400g)
Weather Rating	IP66

Specifications are subject to change without notice