



## PTZ Domes

Outdoor 36X WDR True Day/Night PTZ Dome

# ZC-PT236N-XT

### Features:

- 650 TVL Resolution
- 36x Optical Zoom / 12x Digital Zoom
- True Day/Night
- True Wide Dynamic Range
- 0.01 lux low-light frame integration feature
- 360° continuous pan rotation plus auto-flip feature
- Digital noise reduction
- IP66 rating for all weather conditions



## ZC-PT236N-XT

## Outdoor 36X WDR True Day/Night PTZ Dome

### ■ Mounting Options

Pendant Mount  
ZCA-PMA-Q



Wall Mount  
ZCA-GT200



Straight Wall Mount  
ZCA-GT100



Parapet Mount  
ZCA-PPT



### ■ Specifications

Model		ZC-PT236N-XT
Video Signal Format		NTSC
Image Sensor		Sony Color CCD
Horizontal Resolution		650 TVL
Sync System		Internal / Line Lock
S/N Ratio		> 50 dB
Zoom Range		36x Optical Zoom, 12x Digital Zoom
Effective Pixels		480k
Focal Length		3.4~122.4mm
Focus Mode		Auto / Manual
Iris Control		Auto / Manual
Minimum Illumination		0.1 Lux (Color) / 0.01 Lux (B/W), 50 IRE
Day / Night Performance		True Day / Night, Removable IR Cut Filter
Other Functions		WDR, BLC, SSNR, Stabilization, AGC, WB
Privacy Zone		16 Privacy Masking Zones
Movement Range		Pan 0°~360° (Endless) / Tilt -10°~190°
Speed	Preset	5°~400°/sec
	Jog	0.5°~90°/sec
Presets		256 Presets (16-character label available for each position)
Patterns		8 programmable Patterns (total 480 seconds)
Swings		4 Swings
Groups		8 programmable group tours (each consisting of up to 60 preset steps w/different steps)
Other Pan/Tilt Functions		Auto Flip, Recover Mode
Protocol Options		Ganz-PT, Pelco-D, Pelco-P, Philips, AD-422, JVC, Kalatel (Selectable)
Communication		RS-485
Multi-Language OSD		English, French, German, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Turkish, Chinese
Noise Reduction		2D on / off, 3D on / off
Alarm		8 In / 1 Out
Fan		Yes
Heater		Yes
Resume after Power Loss		Yes
Operation Temperature		-49°F ~ 122°F (-45°C ~ 50°C)
Rated Power		AC 24V / 2.7A (with heater)
Power Consumption		Max 65W (with heater)
Dimensions		6.7" (Ø) x 11.9" (H) / 7.5" (Ø) x 11.9" (H) with sunshield
Weight		5.7 lbs. / 2.6 Kg
IP Rating		IP66
Certifications		CE, FCC, RoHS, IP66

All specifications are subject to change without notice.