

ONVIF
Profile S Compliant




Plug and Play with
PIXEL MASTER
Embedded NVR with
no configuration required

H.264 IP Outdoor Dome IP Camera

GANZ **PixelPro**

Features:

- 1080p HD Resolution
- 1/2.8" Progressive Scan CMOS
- 3-9mm or 3.3-12mm varifocal lens
- Improved picture quality
- **ProSet** System lets you zoom and focus directly from your PC (1080p & 720p)
- Improved low-light performance
- True Day/Night performance
- 18 IR LEDs (IR Models)
- DPC (Defective Pixel Correction) on select models
- Triple power (12VDC / 24VAC / PoE)
- External alarm I/O
- IP66 rated for outdoor use
- Optional wall mount, pendant/conduit mount and heater



GANZ PixelPro

H.264 IP Outdoor Dome Camera Series

Compatible with:



Check our website for an updated list of software partners.

Options


Pendant/Conduit Mount
Model ZNA-CA1
(1 1/2" NPT Pipe)



Wall Mount
Model ZNA-WM2A



4S Box Adapter
Model ZCA-GAP



Heater (optional)
Model ZNA-HD1
(for VGA model only)



Specifications

MODEL	ZN-DT2MTP	ZN-DT2MTP-IR	ZN-DT1MTP	ZN-DT1MTP-IR	ZN-DT1A
Image Sensor	1/2.8" Progressive Scan CMOS				1/2.5" Progressive Scan CMOS
Max. Resolution	1080p			720p	VGA
White Balance	ATW / MANUAL (Preset)				
Digital Zoom	2 ~ 10x (client software)				
Shutter Speed	1/4, 1/10, 1/12.5, 1/15, 1/20, 1/25, 1/30, 1/50, 1/60, 1/100, 1/120, 1/240, 1/480, 1/960, 1/1024, 1/2000 sec				
Day/Night Performance	IR Cut Filter, True Day/Night				
Dynamic Range	50 dB				
IR Illumination	-	18 IR LEDs	-	18 IR LEDs	-
Min. Illumination	0.21 lux (F1.2, 50 IRE), 0 lux IR LED ON				Color: 0.83 lux B/W: 0.07 lux (Slow Shutter ON)
LENS					
Type/ Focal Length	3-9mm Varifocal with P-Iris				3.3-12mm Varifocal
Max. Aperture	F1.2				F1.6
Iris	P-Iris				DC Auto Iris
ProSet Remote Zoom/Focus	Yes				No
ANALOG					
Video Signal (Installation Mode Only)	NTSC/PAL selectable				
Monitor Output	Composite output (BNC), 75 ohm 1Vpp				
NETWORK					
Network	10BASE-T, 100BASE-TX, RJ45				
Image Compression	H.264, MJPEG - 2nd stream only				
Resolution	1920 x 1080 (Full HD), 1280 x 1024 (SXGA), 1280 x 720 (720p), 640 x 480 (VGA), 320 x 240 (QVGA), 704 x 480 (4CIF), 352 x 240 (CIF)				640 x 480 (VGA), 320 x 240 (QVGA), 704 x 480 (4CIF), 352 x 240 (CIF)
Protocol	IPv4, HTTP, SMTP, UPnP, DNS, RTP, TCP, UDP, RTCP, DHCP, ARP, IGMP, ICMP, NTP				IPv4, HTTP, HTTPS, SMTP, UPnP, DNS, Dynamic DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP
Frame Rate	1 fps ~ 30 fps				2.5 fps ~ 30 fps
Web Browser	Internet Explorer 7.0 or above, Firefox, Chrome, PDA / Smart phone				
Security	Password Protection, HTTPS, IP Addressing Filtering				
SDK (API)	HTML based API - ONVIF				
VMD (Video Motion Detection)	User set 4 ROI (Region of Interest), 10 Step Sensitivity				
Alarm Trigger	VMD, External Alarm Input				
Alarm Event	E-mail notification (Snapshot), FTP transfer (Snapshot), SD Card (Snapshot), Video streaming with alarm status				E-mail notification, FTP Uploading, Alarm out
POWER					
12VDC	640mA / Max 7.7 W				460mA
24VAC	500mA / Max 7.5W				5.4W
PoE	140mA / Max 6.7W (IEEE 802.3af compliant)				
OTHER SPECIFICATIONS					
MicroSD Card	-				MicroSDHC
External I/O Terminals	Alarm In x1, Alarm Out x1, Audio In x1, Audio Out x1				
Operating Temperature	-10°F ~ 122°F (-23°C ~ 50°C) / with heater (VGA only) -20°F ~ 122°F				
Weight	2.4lbs. / 1100g				
Weather Rating	IP66				
Dimensions	4.8" (H) x 5.7"Ø / 122mm (H) x 145mm Ø				
Certifications	ONVIF Profile S, CE, FCC, WEEE				

All specifications are subject to change without notice